

PLAST BRICK


MASONRY SYSTEM

DESCRIPTION

Brick and Block Texturing Plaster, where plaster can also be used to build up and straighten walls.

SYSTEM GUARANTEE

15 years



www.masonsplastabrick.co.nz

What is MASONS PLASTABRICK MASONRY SYSTEM?

A masonry render system for smoothing and texturing brick or block. The system provides a hard durable surface which when painted is waterproof and easier to maintain than a standard painted wall.

Advantages

- · Easy to keep clean and weatherproof when painted.
- A wide range of finishes can be achieved.
- · Ideall for modernizing existing older brick or concrete block houses.
- Masons Plastabrick basecoat or lightweight basecoat can be built up to 40mm to straighten walls.

Application

Preparation

All substrates should be clean dry and free from dust, moss or mould. Previously painted substrates can be coated provides the paint is in good condition and well adhered (at applicators discretion and risk). The painted surface should be cleaned then treated with a coat of Masons Plastabrick meshing render to provide adhesion and a gritty surface suitable for plastering.

Flushing

Use basecoat and lightweight basecoat, alternatively skimming render can be applied tightly in a thin application to ensure plaster is forced into the surface and then brought out to a flat finish with extra product. The following day when this has cured a tight coat of skimming render is applied to give a flanking coat and a flat smooth finish.

Texturing

The desired texture from the Masons Plastabrick range can now be applied. Options are 1mm and Adobe or selected pre coloured texture which are painted over with a coat of Limestop and 2 coats of Premium Build.

Painting

Paint in accordance with the chosen texture specification. Premium Build paint is recommended. New block

walls can hold large volumes of water so it is recommended that the wall be protected from rain until painted.

Meshing

150gsm coated fiberglass mesh can be used in the Basecoat plaster and this provides flatter walls with less chance of cracking or block lines showing. It is however not a total guarantee against cracking as a block wall that step cracks can not be 100% prevented by standard 150gsm fibreglass mesh.

Accessories

Premeshed corner beads can be used to form straight corners. Brick Vents are used to provide ventilation into the brick cavity. Bands and mouldings are available.

Special Notes

This system will provide weatherproofing to the wall when properly painted however it is the designers responsibility to provide adequate detailing for penetrations, tops and sealant details for retaining and backfilled walls.